

900 ELLIPTICAL

CARDIO 360™

The C900 Elliptical provides a total body workout for isolated upper-body, lower-body, and upper and lower total-body. a guided workout to engage the upper, core, and lower body with varying resistance.



PREMIUM 900 SERIES



C900 ELLIPTICAL

TECHNICAL SPECIFICATIONS _	Power Source	110V, Self-Generating (with Emerge or Escalate ^s), 220V Option Available (with Envision ¹⁶)
	Cord Length	12' / 3.7 M
	Drive System	Core Drive™
	Total Body Workout	Cardio 360™
	Resistance Source	Hybrid Self-Generating Brake
	Maximum Workload	600 Watts
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Stride Length	21" / 53 cm
	Footpad	Soft Step Cushioned Anti-Fatigue Material
	Exercise Arms	Ergonomic Handles with Moisture-Resistant Sleeves
	Handrail Design	Extended Handrails with Molded Rubber, Moisture-Resistant Grips
_	Side Step Design	Brushed Aluminum with Textured Pattern
_	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar® Compatible
AVAILABLE CONSOLES		Envision ¹⁶ with Compass, Envision ¹⁸ , Emerge, Escalate ⁹
ASSET TRACKING		EcoFit Compatible
Cardio 360™	Upper Body Isolation	Yes
	Lower Body Isolation	Yes
	Total Body	Yes
SAFETY	Side Steps	Standard
	Extended Handrails	Standard
	Activity Guard (removable)	Standard
REGULATORY APPROVAL	S	ETL UL1647, CSA, CE, EN957, FCC
EXTRAS	Accessories	Water Bottle Holder, Accessory Tray, Over Molded Reading Rack/Tablet Holder
PHYSICAL SPECIFICATIONS 	Footprint	66" L x 34" W x 64" H / 167.64 cm x 86.36 cm x 162.56 cm
	Active Footprint	73" L x 34" W x 64" H / 185.42 cm x 86.36 cm x 162.56 cm
	Q-Factor	2.5" / 6.35 cm
	Machine Weight	375 lbs / 170 kg
	Shipping Weight	423 lbs / 192 kg
	Maximum User Weight	400 lbs / 181 kg
	Step-Up Height	8" / 20.32 cm
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Classification	Commercial (all dues paying facilities, regardless of usage)
	Frame	Lifetime
	Parts	3 Years
	Labor	3 Years

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.

